

GENERAL		PKT-23
Frequency Range CB		476.425-477.4125 MHz Preset 80 Channels
Number of Channels		8 ch
RF Power Output		1.5W (ERP)
Battery Life (5-5-90)		Approx. 15 hours (Battery Saver Off)
Dimensions (W x H x D)	Excluding antenna	46.0 x 85.0 x 21.0 mm
Weight	with Battery	Approx. 110 g

Standards	MIL 810C Methods	MIL 810D Methods	MIL 810E Methods	MIL 810F Methods	MIL 810G Methods
Low Pressure	500.1/ I	500.2/ I, II	500.3/ I, II	500.4/ I, II	500.5/ I, II
High Temperature	501.1/ I, II	501.2/ I, II	501.3/ I, II	501.4/ I, II	501.5/ I, II
Low Temperature	502.1/ I	502.2/ I, II	502.3/ I, II	502.4/ I, II	502.5/ I, II
Temperature Shock	503.1/ I	503.2/ I	503.3/ I	503.4/ I, II	503.5/ I
Solar Radiation	505.1/ I	505.2/ I	505.3/ I	505.4/ I	505.5/ I
Rain	506.1/ I, II	506.2/ I, II	506.3/ I, II	506.4/ I, III	506.5/ I, III
Humidity	507.1/ I, II	507.2/ II, III	507.3/ II, III	507.4	507.5/ II
Salt Fog	509.1/ I	509.2/ I	509.3/ I	509.4	509.5
Dust	510.1/ I	510.2/ I	510.3/ I	510.4/ I, III	510.5/ I
Vibration	514.2/ VIII, X	514.3/ I	514.4/ I	514.5/ I	514.6/ I
Shock	516.2/ I, II, V	516.3/ I, IV	516.4/ I, IV	516.5/ I, IV	516.6/ I, IV
International Protection Standard					
Dust & Water Protection	IP54				